
# **ELLIPTIC**





### **FEATURES**

MATERIAL
FINISH
RATED POWER
WORKING VOLTAGE
RADIANCE ANGLE
MOUNTING
CONNECTION
LAMP LIFE
DIMENSION
OPERATIN TEMP
CONTROL

Die-cast aluminum White, Black, Silver 6W 100-240 V 50/60Hz 15°, 24°, 36° Ceiling recessed Indoor rated connections 50,000 Hrs Ø150 x 88mm(CutoutØ80mm) -30° C - +50° C On/Off, Triac, 1-10V, Dali



LIGHTING





## **ELECTRICAL DATA**

POWER CONSUMPTION	6W
SUPPLY VOLTAGE	AC 100-240V
COLORS	2700K, 3000K, 4000K, 5000K
CRI	90
LUMEN	85lm/W

Contractor

### DIMENSIONS





### **ORDERING LOGIC**

PRODUCT	WATTAGE	COLOR TEM	IPERATURE	BEAM ANGLE	FINISH	CUSTOM
ELP 06	6 - 6W	(CT27)	2700K	15 - 15°	WH - WI	hite xx
		(CT30)	3000K	24 - 24°	BK - Bla	ack
		(CT40)	4000K	36 - 36°	SL - Sil	lver
		(CT50)	5000K			

Sample: ELP 06 - 6 - CT27 - 15 - WH - XX