FLOOD LIGHT

RFL-MONO



IP66 WATER ϵ

YYZ RFL is a unique square-shaped luminaire in power LED version providing precision optical systems which gives very low glare rating, while reducing light pollution and specially designed for landscapes and in unique structural design shape. Theses luminaires are designed to offer functional, a wide range of lighting solutions and dramatic highlighting of the architectural facades, landscapes, trees through the superior finishing as well highest efficiency with a long service life. This exterior ground spike luminaries are made in aluminum body and can achieve the desired effect in a wide range of applications with high quality optical systems and for direct lighting. These are mainly used in outdoor landscape, building advertising, inside or outside of building wall, huge architecture, huge bridge guardrail.

FEATURES

MATERIAL Anodized extruded aluminum

FINISH Black
RATED POWER 360W
WORKING VOLTAGE 220 Vac
LED QUANTITY 168Nos

BEAM ANGLE 3.5°, 8°, 15°, 20°, 35°, 45°, 60°

ROTATION ANGLE 130°

MOUNTING Surface mount

CONNECTION Outdoor rated connections

LAMP LIFE 50,000 hrs

DIMENSIONS 448mm(L)x418mm(W)x273mm(H)

OPERATION TEMP -40° C $-+50^{\circ}$ C STORAGE TEMP -40° C $-+80^{\circ}$ C CONTROL Dmx, On-Off


ELECTRICAL DATA


POWER CONSUMPTION 360W SUPPLY VOLTAGE 220Vac

COLORS 2700/3000/4000/5000K/Red/Green/Blue

CRI >80 LUMENS 75-78lm/W

DRAWING





ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE		OPTIC			VOLTAGE		FINISH		CUSTOM
RFL	360 - 360W	(CT 27)	2700K	3.5	-	3.5°	220 -	220V AC	BK -	Black	XX - XXX
		(CT 30)	3000K	8	-	8°					
		(CT 40)	4000K	15	-	15°					
		(CT 50)	5000K	20	-	20°					
		(RE)	Red	35	-	35°					
		(GR)	Green	45	-	45°					
		(BL)	Blue	60	-	60°					

Sample: RFL -360 - CT 27 - 3.5 - 220 - BK - XX





