

VERTEX K23

VTX K23



YYZ Vertex K23 series high brightness and easy installation for architectural outdoor solution, used milky diffuse cover and aluminum and diffuser end cap, with built in DMX512 module. The modular system available in 250mm, 500mm or 1000mm lengths and can be customized as per project requirement. All cables can be hidden into channel, IP67-rated, UV resistant and designed to withstand outdoor element, applicable for various architectural environment.



FEATURES


LIGHT SOURCE	5050 Led
LED QUANTITY	48 Leds / mtr
FINISH	Aluminum
WORKING VOLTAGE	24 Vdc
RATED POWER	12W/mtr
RADIANCE ANGLE	120°
DIFFUSER	Milky
LAMP LIFE	50000 hrs
MOUNTING	Mounting clip / Channel
CONNECTION	Outdoor rated connections
DIMENSIONS	250, 500, 1000(L) x 23(W) x 50.7(H)
MAX DAISY RUN	7 mtr max daisy chain
OPERATION TEMP	-25° C - +50° C
STORAGE TEMP	-40° C - +70° C
CONTROL	DMX512

- EPISTAR**
LED Quality
- 24 VOLTS**
Working Voltage
- 12W / mtr**
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	12W/mtr
SUPPLY VOLTAGE	24 Vdc
SUPPLY CURRENT	240V ac
COLORS	MONO/RGB/RGBW
CRI	80+
LEDS / 3.3FT	48

DIMENSION



ORDERING LOGIC

PRODUCT	POWER	CONTROL	PIXEL	COLOR TEMPERATURE	VOLTAGE	FIXTURE LENGTH	MOUNTING	CONNECTION	CUSTOM
VTX K23	12 - 12W	ON - ON/OFF DX - DMX512	8 - 8 Pixel Add. 4 - 4 Pixel Add. 1 - 1 Pixel Add.	(MONO) MONO (RGB) RGB (RGBW) RGBW	24 (24 Vdc)	1 250MM 2 500MM 3 1000MM X CUSTOM	CLP - Clip CHL - Chanel	OC - Outdoor Connector	XX

Sample: VTX K23 - 12 - DX - 8 - RGBW - 24 - 3 - CLP - OC - XX