

LARVA SPIKE SPOT

LRV SP

Mono IP66 CE

Exterior directional spotlight ideal for highlighting landscape features. Engineered with special optical system to provide different beam distribution and glare free illumination.



FEATURES

MATERIAL	Aluminum
TRIM FINISH	Black
RATED POWER	7W
BEAM ANGLE	15°, 18°, 24°, 36°
MOUNTING	Spike mounted
LAMP LIFE	50,000 hrs
DIMENSIONS	Ø45 x 500mm
OPERATION TEMP	-20° C - +50° C
CONTROL	Switched, 1-10V, Dali, Triac (Driver based)
SDCM	2

CREE
LED Quality


150mA
Working Current

7W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	7W
COLORS	2700K, 3000K, 4000K
CRI	>90
LUMEN	477lm

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	BEAM ANGLE	FINISH	CUSTOM
LRV SP	7 - 7W	(CT27)	2700K	SW - Switched	15 - 15°	BK - Black XX - XX
		(CT30)	3000K	AN - 1-10V	18 - 18°	
		(CT40)	4000K	DA - Dali	24 - 24°	
				TR - Triac	36 - 36°	

Sample: LRV SP - 7 - CT27 - SW - 15 - BK - XX