

ROVER SURFACE MOUNTED LIGHT

RVR-R

Mono IP54 CE

YYZ Rover is surface mounted LED downlight is with symmetric light distribution to achieve an effective task, accent or ambient lighting. These downlights are also suitable for all commercial lighting applications as well as public indoor space where there is limited space in ceiling. It is available in white and black finishes.

FEATURES

| | |
|-----------------|-------------------------|
| MATERIAL | Die-cast aluminum |
| FINISH | White, Black |
| WORKING VOLTAGE | 100-240V |
| RATED POWER | 75W |
| LAMP | E27 |
| LAMP LIFE | 50,000 hrs |
| MOUNTING | Surface mounted |
| CONNECTION | Indoor rated connection |
| DIMENSIONS | Ø108 x140mm |
| OPERATION TEMP | -30° C - +50° C |
| CONTROL | On/Off |



V 240V AC
Working Voltage

W 75W
Rated power

ELECTRICAL DATA

| | |
|-------------------|---------------------|
| POWER CONSUMPTION | 75W |
| SUPPLY VOLTAGE | 100-240Vac |
| COLORS | 2700K, 3000K, 4000K |
| CRI | 90 |

DIMENSIONS



ORDERING LOGIC

| PRODUCT | WATTAGE | LAMP | COLOR TEMPERATURE | VOLTAGE | FINISH | CUSTOM | |
|---------|----------|-----------|-------------------|---------|-------------|------------|-----------|
| RVR-R | 75 - 75W | E27 - E27 | (CT27) | 2700K | AC - 240VAC | WH - White | XX - XXXX |
| | | | (CT30) | 3000K | | BK - Black | |
| | | | (CT40) | 4000K | | | |

Sample: RVR-R - 75 - E27 - CT 27 - AC - WH - XX