

# DOME SERIES

## DOE-R150 L

**Mono** IP54 CE

YYZ Dome series of architectural downlight features glare free performance with the ultra wide beam angle. Available in variety of sizes to accommodate wattage. Making it versatile for applications with ceiling heights.

### FEATURES

MATERIAL	Aluminum
FINISH	White
RATED POWER	18W
WORKING CURRENT	700mA
RADIANCE ANGLE	90°
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	Ø162 x 60mm (Cutout Ø150mm)
OPERATING TEMP	-20° C - +50° C
CONTROL	Non-Dim, 1-10V, Dali



SAMSUNG  
LED Quality

700mA  
Working Current

18W  
Rated power

### ELECTRICAL DATA

POWER CONSUMPTION	18W
SUPPLY VOLTAGE	220-240V AC
COLORS	2700K, 3000K, 4000K
CRI	80, 90
LUMEN	2200-2400lm @ 18W

### DIMENSIONS



### ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	BEAM ANGLE	FINISH	REFLECTOR FINISH
DOE R 150L	18 - 18W	(CT27)	2700K	90 - 90°	WH - White
		(CT30)	3000K		XX - Custom
		(CT40)	4000K		
					MA - Matt
					WH - White
					BK - Black

Sample: DOE R 150L - 18 - CT27 - 90 - WH - MA