

LINEAR INGROUND

LIG

Mono IP67 WATER PROOF IK10 CE

YYZ in-ground linear light series is your next-level choice for outdoor floor applications, featuring the unrivaled resistance to vandalism, UV, water, corrosion, and slipping, as well as the elevated visual experience suitable for a direct view. Paving it on roads, you can anticipate a dot-free, glare-free, and well-lit nightscape presented in countless possibilities. Constructed with a visionary structural design, having the IP68-rated LED strip housed in a solid metallic casing, distinctively further sealed by a thickened silicone diffuser, all combine to be a fusion of robust and waterproof. It's stress-free for you to apply it to walkways, driveways, squares, parking lots, landscapes, fountains, and more, where frequently suffer the impact from high heels and vehicles, or water splashing or soaking may occur.



FEATURES

FINISH	Stainless steel
WORKING VOLTAGE	24 V DC
RATED POWER	15W/m
BEAM ANGLE	110°
AVAILABLE LENGTH	504mm, 1004mm
MOUNTING	Floor recessed mounted
DIMENSIONS	L 504, 1004 x W 85 x H 100mm
OPERATION TEMP	-40° C - +50° C
LAMP LIFE	50,000 hrs
DRIVER OVER RATE	10000Kg
BODY COLOR	Stainless steel
CONTROL	On/Off, 1-10V, Triac, Dali, DMX

CREE
LED Quality


24 VOLTS
Working Voltage

14.4 W / m
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	14.4W/ m
INPUT VOLTAGE	24V DC
COLORS	2700K, 3000K, 3500K, 4000K, 5000K

DIMENSION



ORDERING LOGIC

PRODUCT	COLOR TEMPERATURE	VOLTAGE	CONTROL	FIXTURE LENGTH	
LIG 15	(CT27)	2700K	24 - 24VDC	SW - On/Off AN - 1-10V TR - Triac DA - Dali	50 - 504mm 100 - 1004mm
	(CT30)	3000K			
	(CT35)	3500K			
	(CT40)	4000K			
	(CT50)	5000K			

Sample: LIG - CT27 - 24 - SW - 50

LINEAR INGROUND LIG

