

FLEX PANEL LED TUNABLE WHITE



LFX-FLEX-TW


3M TAPE

IP54



48W (Max)

YYZ flex panel offers field customizable LED back lighting solution. The flexible panel can be folded and shaped to suit project needs. Versatile design use in an indoor environment. Choices of color temperatures with dimming using appropriate driver.



FEATURES

OPERATING VOLTAGE	24 Volts DC
OPERATING TEMPERATURE	-20°C to 50°C
LED QUANTITY	400 LEDs / Sheet
FINISH	WHITE
LAMP LIFE	50,000 hrs
AVAILABLE IP RATING	IP54
CONTROL	DMX / PWM / 0-10V Dimming
BEAM ANGLE	120°
COLORS	2700K to 6000K
WARRANTY	5 Years

400LEDs / Sheet
LED Quantity

24V DC
Operating Voltage


48W (Max)
Rated Power

3M Tape on the back
Mounting

ELECTRICAL DATA

POWER CONSUMPTION	48W (Max)
SUPPLY VOLTAGE	Low Voltage DC24V
LUMEN PER PIECE	4000Lm / pcs
CRI	80+

COLOR TEMPERATURE DATA



ORDERING LOGIC

PRODUCT SERIES	TYPE	POWER	COLOR TEMPERATURE	LED TYPE	BIN	NO. OF LED	VOLTAGE	CIRCUIT	PCB	CRI	NO OF LED ROWS	CONNECTION
LFX	W - WET RATED (IP54)	48 - 48 W / Sheet	TW - Tunable White (2700K - 6000K)	2835	Z3	400 - 400 LEDs/Sheet	24-24V	CV - Constant Voltage	250 - 250mm	N - Standard (80)	10	OC - Outdoor Connector




MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER SHEET
R - Regular	C - Color Mixed	T - Top	L - Low	W - White	OD5 - 500mm

Sample: LFX-W-48-TW-2835-Z3-400-24-CV-250-N-10-OC-RCTLWOD5

FLEX PANEL LED TUNABLE WHITE

LFX-FLEX-TW

DIMENSIONS



Protective Bumper