MYRIAD TRACK LIGHT

MRD-97



IP20

 $C \in$

YYZ Myriad track lights houses driver unit to the track adapter allowing better thermal performance and hence the light output. Options of various optics on a 1-circuit, 3-circuit $adapter\,with\,wide\,range\,of\,dimming\,options\,makes\,the\,system\,versatile.\,The\,aluminum\,housing\,adapter\,with\,wide\,range\,of\,dimming\,options\,makes\,the\,system\,versatile.$ that facilitates efficient performance and is flexible to rotate.







FEATURES

MATERIAL Aluminum Black, White TRIM FINISH

20W RATED POWER

WORKING VOLTAGE 220-240V 50/60Hz 15°, 24°, 36°, 60° **RADIANCE ANGLE** MOUNTING Track mounted

CONNECTION Indoor rated connections

LAMP LIFE 50,000 Hrs

DIMENSION Ø97 x 65 x 155mm -20° C - +50° C OPERATIN TEMP CONTROL On/Off, 1-10V

ELECTRICAL DATA


POWER CONSUMPTION 20W

SUPPLY VOLTAGE 220-240VAC

2700K, 3000K, 4000K COLORS

90 CRI LUMEN 1464lm

DIMENSIONS



ORDERING LOGIC

PRODUCT	CONTROL	WATTAGE	COLOR TEMPERATURE		VOLTAGE	BEAM ANGLE		FINISH	
MRD-97	ON/OFF	20 - 20W	(CT27)	2700K	240VAC	15 -	15°	BK	- Black
	1-10V		(CT30)	3000K		24 -	24°	WH	- White
			(CT40)	4000K		36 -	36°		
						60 -	60°		

Sample: MRD-97 - ON/OFF - 20 - CT27 - 240 - 15 - BK