

EDIFICE INGROUND LIGHT

EFE

Mono IP68 IK10

YYZ Edifice inground lights feature robust construction with body in heavy duty die-cast aluminium and 304/316 marine grade stainless steel. High performance adjustable optics render precise beam of light suited for wide range of facade and landscape applications.



FEATURES

MATERIAL	Die cast aluminum body with stainless steel frame
RATED POWER	18W, 22W
WORKING VOLTAGE	100-277V AC
BEAM ANGLE	9°/18°/36°/58°
MOUNTING	Floor recessed
LAMP LIFE	L90, B10, 65, 000hrs
DIMENSIONS	Ø200x150mm
OPERATION TEMP	-20° C - +50° C
CONTROL	Dali, On-Off, 1-10V
SDCM	SDCM3, SDCM2 (On request)
DRIVER OVER	4000kg@20km/hr


CREE/OSRAM
LED Quality

100-277V AC
Working Voltage


18W/22W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	18W, 22W
SUPPLY VOLTAGE	100-277V AC
COLORS	2700K, 3000K, 4000K, 5000K
CRI	80+
LUMEN	90-95lm/W



DIMENSION



ACCESSORIES



Recessed Box



IP 68 Connector



Square cover

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	VOLTAGE	BEAM ANGLE	IP RATE	FINISH	ACCESSORIES	CUSTOM
EFE	18 - 18W	(CT27)	2700K	9 - 9°	68 - IP68	SS - Stainless Steel BK - Black	RB - Recessed Box	XX - XX
	22 - 22W	(CT30)	3000K	18 - 18°			CN - IP 68 Connector	
		(CT40)	4000K	36 - 36°			SC - Square cover	
		(CT50)	5000K	58 - 58°				

Sample: EFE - 18 - CT27 - AC - 9 - 68 - SS - RB - XX