

# ATRIUM IP SURFACE MOUNT

## ATR IP-S

IP54, IP65

Atrium IP series luminaires are designed for demanding clean room environments like food processing, professional kitchen areas, hospital environments etc. Body constructed in sheet steel powder coated to white RAL 9016. Options of Tp(a) & Tp(b) diffusers and tempered glass to suit application requirements. Wide range of ceiling compatibility to suit various types of ceilings.



### FEATURES

MATERIAL	CRCA Sheet Steel
FINISH	White Epoxy polyester powder coated in white(RAL 9016)
RATED POWER	30W, 34W, 36W, 40W, 50W, 60W, 75W
WORKING VOLTAGE	220-240V AC
RADIANCE ANGLE	180°
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	L70,B20 50,000 hours
DIMENSION	595mm x 595mm x 85mm, 1200x300x85mm
OPERATING TEMP	-20° C - +50° C
CONTROL	On/Off, Dali, 1-10V, Emergency Kit

SAMSUNG/LUMILEDS  
LED Quality


220-240VAC  
Working Voltage

30W/34W/36W/40W/50W/60W/75W  
Rated power

### ELECTRICAL DATA

POWER CONSUMPTION	30W, 34W, 36W, 40W, 50W, 60W, 75W
SUPPLY VOLTAGE	220-240V AC
COLORS	3000K/4000K/6500K
CRI	>80
DELIVERED LUMENS	120lm/W
SDCM	3SDCM, 2SDCM (on request)

### DIMENSIONS



L	W	H
595	595	85
1200	300	85

### ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	INPUT VOLTAGE	FINISH	CONTROL	DIFFUSER	SIZE - L x W	IP RATING
ATR IP-S	30 - 30W	(CT 30) 3000K	220-240VAC	WH - White	SW - On/Off	A - Tp(a)	A - 595x595	54 - IP54
	34 - 34W	(CT 40) 4000K		XX - Custom	DA - Dali	B - Tp(b)	B - 1200x300	65 - IP65
	36 - 36W	(CT 65) 6500K			AN - 1-10V	G - Tempered Glass		
	40 - 40W	(CTXX) CUSTOM			EM - Emergency Kit			
	50 - 50W							
	60 - 60W							
	75 - 75W							

Sample: ATR IP-S - 30 - CT30 - 220 - WH - SW - A - A - 54