

PANDORA MAGNETIC TRACK LIGHT

PDA

Mono IP40 CE

Pandora series of Track light features a family of attachments to meet diverse lighting requirements. Tools free magnetic insets includes spotlight, cylindrical & circular pendants, wall wash spot, linear downlight and diffused lights. Preferred choice for wide range of commercial, architectural and hospitality spaces.



FEATURES

MATERIAL	Aluminum + PC
BODY FINISH	Black, White
RATED POWER	9W
BEAM ANGLE	40°
VOLTAGE	220-240VAC, 50/60Hz
MOUNTING	Track mounted
DIMENSIONS	195x22x73mm
OPERATION TEMP	-20° C - +50° C
CONTROL	On/Off, Dali, 1-10V


BRIDGELUX
LED Quality

9W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	9W
SUPPLY VOLTAGE	220-240VAC
COLORS	2700K, 3000K, 4000K, 5000K
CRI	90
LUMEN	85lm/W

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	BEAMANGLE	FINISH	CUSTOM
PDA	9 - 9W	(CT27) 2700K	ND - Non Dimmable	40 - 40°	BK - Black	XX - XX
		(CT30) 3000K	DA - Dali		WH - White	
		(CT40) 4000K	AN - 1-10V			
		(CT50) 5000K				

Sample: PDA - 9 - CT30 - ND - 40 - BK - XX