

HERMETIC 80

HMT 80

Mono IP65 IK08 CE

YYZ Hermetic is a tough and corrosion resistant surface/suspension mounted weatherproof luminaire suitable for application areas of high humid and dusty atmospheres. HMT1 is made of die-cast aluminum housing and a thick injection moulded polycarbonate cover, ensuring IK08 impact resistance. Wide beam optic and high efficiency makes it the best choice for use in garages, factories etc.



FEATURES


MATERIAL	Polycarbonate
FINISH	Grey
RATED POWER	20W (600mm), 30W (1200mm), 25W, 50W (1500mm), 30W, 50W (1800mm)
WORKING VOLTAGE	36-42V DC
RADIANCE ANGLE	120°
MOUNTING	Surface mounted
CONNECTION	Outdoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	600, 1200, 1500, 1800(L) x 125 (W) x 88(H)mm
OPERATING TEMP	-25° C - +50° C
CONTROL	On/Off, 1-10V, Dali

- SAMSUNG/LUMILED LED Quality
- 36-42V DC Working Voltage
- 20W/25W/30W/50W Rated power

ELECTRICAL DATA

POWER CONSUMPTION	20W (600mm), 30W (1200mm), 25W, 50W (1500mm), 30W, 50W (1800mm)
SUPPLY VOLTAGE	200-240V AC
COLORS	3000K, 4000K, 5000K, 6000K
CRI	80, 90
LUMEN	100lm/W, 130lm/W

DIMENSION



Power	Length	Width	Height
20W	600mm	80mm	75mm
30W	1200mm	80mm	75mm
25W, 50W	1500mm	80mm	75mm
30W, 50W	1800mm	80mm	75mm

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	DRIVER	FIXTURE SIZE -L x W x H	LUMEN
HMT 80	20 - 20W (600mm)	(CT30) 3000K	ND - Non-Dimmable	20W - 600 x 80 x 75mm	100 - 100lm/W
	30 - 30W (1200mm)	(CT40) 4000K	AN - 1-10V	30W - 1200 x 80 x 75mm	130 - 130lm/W
	25 - 25W (1500mm)	(CT50) 5000K	DA - Dali	25W, 50W - 1500 x 80 x 75mm	
	30 - 30W (1800mm)	(CT60) 6000K		30W, 50W - 1800 x 80 x 75mm	
	50 - 50W (1800mm)				

Sample: HMT 80 - 20 - CT30 - ND - 20W - 100